

Sylvagen Specification Sheet

Acceptable Material Grades

Recycled wood to conform with the below specification for use as recycled feedstock in the panel board manufacturing industry or as wood-fuel for combustion in boilers compliant with the Waste Incineration Directive.

Moisture Content will range from 10-30%, the Supplier should take all appropriate steps to ensure that the Moisture Content is not increased due to insufficient storage or transportation measures.

Wood must not contain hot spots and must be free from any contaminants that could lead to fire. If unsure, please speak to a member of staff and check for hot spots with temperature gun.

If maximum quantity of manufactured board in a load exceeds 40% Sylvagen must be contacted in advance of loading.

Grade A

EWC Codes: 03 01 05 – Wastes from wood processing and the production of panels and furniture /15 01 03 – Waste Wood Packaging

Soft Unpainted White Wood including - Pallets, Off cuts, Scaffold Boards, Joists*, Untreated Floor Boards, Skids, Crates and Boxes. May contain small amounts of nails and metal fixings, paints and surface coatings are not acceptable.

Packaging and pallets marked with 'MB' will have been treated with Methyl Bromide, and will be deemed Hazardous. Sylvagen will not accept this in the feedstock.

Grade B

EWC Codes: Grade A + 17 02 01 – Construction & Demolition/19 12 07 – Wood not containing dangerous substances from waste management facility

All Grade A Material

Window Frames & Doors*, Roof Trusses*, Painted Soft Wood*, Treated Floor Boards.

May contain small amounts of nails, metal fixings, small amounts of paints and surface coatings are acceptable (non CCA or Creosote).

Grade C

EWC Codes: Grades A + B plus 20 01 38 - Municipal/Industrial Waste

All Grade A and B Material

Fencing products, flat pack furniture, MDF, plywood, OSB, fibreboard, Civic Amenity Waste, Formica, Kitchen Furniture.

May contain small amounts of nails, metal fixings, paintings, plastics, glass, binders, glues, grit, surface treatments (non CCA or Creosote).

* From 1st September 2023, Demolition waste wood (RPS 250 Withdrawal)

Potentially hazardous waste wood items are:

barge boards; external fascias; soffit boards; external joinery (wooden windows and conservatories); external doors; roof timbers; tiling and cladding battens; timber frames and joists from pre-2007 buildings.

Sylvagen will NOT be able to accept the above items on our current destination permits.

Unacceptable Materials

Recycled wood will face immediate rejection or charges if it contains any of the following:

Creosote Treated Products, CCA Treated Railway Sleepers, Telegraph Poles or Fence Panels, Asbestos Insulation Board and any other Hazardous Waste.

Contamination in Loads

Recycled wood will face rejection or picking charges if deemed to contain the following:

Unidentifiable material, Batteries, Hot material, Paper, Foam, Textiles, Felt, Tar, Rubber, Polythene, Cardboard, Black Bags, Plastic Coated Wire, Degraded Wood, Burnt or Charred Material, Excessive Fines, Nails, Metal Fixings, Plastics, Glass, Grit Mud and Stones.



Sylvagen Specification Sheet

Please see below extract WRA Grades of Waste Wood which is a useful informative guide detailing the various grades of Waste-Wood.

GRADE	Typical Markets	Typical Sources of raw material for recycling and/or recovery	Typical Materials	Typical non-wood content prior to processing	Notes
Grade A Pre-Consumer Waste Wood (*1) and untreated wooden packaging = Clean un- treated	A feedstock for the manufacture of professional and consumer products such as animal bedding, equine and landsaping surfacing. May also be used as a fuel in domestic and non-IED Chapter IV biomass installations and for the manufacture of pellets and briquettes.	Wood Product Manufacturing, Distribution, Retailing, Packaging and Secondary manufacture, e.g. joinery and pallet reclamation.	Solid softwood and hardwood. Packaging waste, scrap pallets, packing cases and cable drums. Process off-cuts from the manufacture of virgin/sawn timber and untreated board products.	Nails and metal fixings. Minor amounts of non-hazardous surface coatings, such as water-soluble paint.	This is a waste as defined the waste regulations. Do not require an IED Chapter installation and should not contain any treated or low grade material.
Grade B Business waste wood = Treated Non-hazardous	This is the preferred feedstock for industrial wood processing operations such as the manufacture of panel board products. Can also be used for IED Chapter IV biomass.	As Grade A, plus construction and demolition operations, skip operators, transfer stations.	May contain Grade A material as above plus building and demolition materials and domestic furniture made from solid wood.	Nails and metal fixings. Some paints, plastics, glass, grit, non-hazardous coatings, binders and glues. Limits on treated or coated materials as defined by end users and IED.	This is mostly solid wood. Some feedstock specifications contain a 5% to 10% limit on former par products such as chipboar MDF and plywood. Is a waste for the requirement of Waste Management Regulations. Will require a IED Chapter IV compliant installation for biomass. Any of the Items listed in t WIRA Waste Wood Assessment Guidance as 'Potentially Hazardous' ("Z must be segregated and tested to prove that they a non-hazardous. Otherwise they must be categorised i Grade D – Hazardous.
Grade C Municipal waste wood = Treated Non-hazardous	For use in the IED Chapter IV biomass installations and for panel board in controlled volumes.	All above plus municipal collections, transfer stations and HWRCs.	All of the above plus flat pack furniture made from board products and DIY materials.	Nails and metal fixings. Paints, coatings and glues, paper, plastics and rubber, glass, grit. Coated and treated timber (non CCA or creosote).	This is mostly board products. Mainly suitable IED Chapter IV compliant biomass installations, but also suitable for panel boa manufacture with correct processing and blending. a waste for Waste Management Regulations.
Grade D Hazardous waste wood = Treated hazardous	Requires disposal at facilities licensed to accept hazardous waste.	Waste wood from hydraulic engineering, such as wood from docks. Waste wood from industrial applications such as cooling tower timbers, woodblock flooring or moulds Waste wood from boats, carriages and trailer beds Waste wood treated with CCA or crososte Any of the items listed in the WRA Waste Wood Assessment Guidance as Potentially Hazardous (*2) must be segregated and tested to prove that they are non-hazardous. Otherwise they must be categorised as Grade D - Hazardous	Agricultural fencing, telegraph poles, railway siegeprs. 2 Potentially hazardous waste wood items are: barge boards; external fascias; soffit boards; external joinery (wooden windows and conservatories); external doors; roof timbers; tiling and cladding battens; timber frames and joists from pre-2007 buildings	Copper chrome arsenic (CCA) preservation treatments and creosote.	These materials must be segregated and consigned hazardous to sites permitt to accept hazardous wood.